

SKG-IKOB PRODUCTCERTIFICATE

404.213.03

Date of issue: 20-06-2022



Certificate holder

Fuhr GmbH & Co KG
Carl Fuhr Straße 12
D-42579 Heiligenhaus
T: +49 (0) 2056 5920
E: info@fuhr.de
I: www.fuhr.de



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

cylinder mortice multipointlock with escapefunction wo electromechanical

delivered under logo / brand:

FUHR

delivered under type- and / or article number:

835P / 836P - type 10 - SKG2

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

(at which the symbol for escape doors or the code EN179/EN1125 is added.)



For SKG-IKOB

A blue ink handwritten signature, likely belonging to ir. H.A.J. van Dartel.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

CERTIFICATE

SKG-IKOB PRODUCTCERTIFICATE

Fuhr GmbH & Co KG
Number: 404.213.03

page 2 of 2

1. PRODUCT

cylinder mortice multipointlock with escapefunction wo electromechanical

PRODUCT TYPE

multipoint lock

2. TECHNICAL SPECIFICATION

Operating:	Mechanical and electrical operation
Construction:	1 forend with main lock with square bolt and var. type latches + 2 additional hook bolts
System:	self-locking, key or handle operated lockable by 17 mm profile cylinder or electronic PZ: 92 mm , BS: 35~80 mm
Material:	forend and lock cases: steel zinc coated
Dimension:	wood: forend: 1800/2405x(U)20~30x3 mm aluminium and PVC: forend: 1800/2405x(U)16~30x3 mm lock cases: 200xBS+18x15 / 135x40x15 mm
Fixing:	wood: forend in LH 4x40 mm, in NH 4x50 mm PVC: forend: 4 mm in steel reinforcement min. 1,5 mm aluminium: forend: 4 mm OR M5 with clamp plate (Wicona)
Intended use:	wood, PVC, metal, door-inward-opening, door-outward-opening ATTENTION: This lock only achieves its SKG star rating if an anti-drilling is provided to prevent grip / push-bar manipulation. If glass is used in the door element (incl. side-light), this must at least comply with class P4A in combination with FUHR keepers OR keeperstrip: wood: 404.612.06 pvc: 404.611.01 metal: 404.613.02

3. DELIVERY

The delivery includes an installation instruction:
1-0800-007 OR 1-0800-008 / 1-0800-027 OR 1-0800-006

4. PERFORMANCES

A cylinder mortice multipointlock with escapefunction wo electromechanical according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this cylinder mortice multipointlock with escapefunction, w/o electromechanical is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this cylinder mortice multipointlock with escapefunction, w/o electromechanical is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).