

SKG-IKOB PRODUCTCERTIFICATE

404.612.01

Date of issue: 20-06-2022



Certificate holder

Fuhr GmbH & Co KG
Carl Fuhr Straße 12
D-42579 Heiligenhaus
T: +49 (0) 2056 5920
E: info@fuhr.de
I: www.fuhr.de



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

keeper set

delivered under logo / brand:

FUHR

delivered under type- and / or article number:

type 3/4/10/11 - SKG3
RFHS xxxx + RFHSZ 13517 + RCHSZ 14382 + RCHSZ 57991
RFHS xxxx + RFHSZ 13517 + RJVH xxxx Z
RL xxxx(ZG)

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, appearing to be "ir. H.A.J. van Dartel", written over a light blue background.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

CERTIFICATE

1. PRODUCT

keeper set

PRODUCT TYPE

lock striker plate

2. TECHNICAL SPECIFICATION

Operating:	
Construction:	main boxkeeper and additional boxkeeper with keeperplate
System:	main boxkeeper: double hole for latch and square bolt additional boxkeeper: single adjustable hole for additional hookbolt
Material:	keeperplate: steel zinc box keepers: zamak
Dimension:	keeperplate (double): 220x24x3,0 mm mainkeeper: 200x24x22 mm additional keeper: 120x24x18,5 mm
Fixing:	mainkeeper: 5 point, application class 2: 2 screws 4x40 mm oblique, 3 screws 4x30 mm straight class 3: 2 screws 4x50 mm oblique, 3 screws 4x50 mm straight additional boxkeeper: 4 point: application class 2: 2 screws 4x40 mm oblique, 2 screws 4x30 mm straight class 3: 2 screws 4x50 mm oblique, 2 screws 4x50 mm straight
Intended use:	wood, door-inward-opening, door-outward-opening for wooden doors and windows in combination with FUHR multipoint locks with additional hookbolts

3. DELIVERY

The delivery includes an installation instruction:
M2-SKG-DE-NL_08_19-4

4. PERFORMANCES

A keeper set according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this keeper set is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this keeper set is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
